

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 45/13 Mi

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Working Pressure	13 bar
Free Air Delivery (at 13 bar)	* 5,45 m ³ /min.
Shaft Power (at 13 bar)	45 kW
Max. Ambient Temperature	40°C
Electric Motor	45 kW/60 hp; 2 Pole (2965 rpm); 400V; 50Hz; IP55; F Insulation; B3 Built; IE3 Class
Cooling System	Air Cooling
Fan Motor & Capacity	1,5 kW; (1435 rpm); 400V; 50Hz; --- 7840/289 (m ³ /h)/Pa
Airend	SCA13 – TMC(ITALY)
Hydraulic Connections	VITILLO(ITALY)
Cooler	AKG(GERMANY)
Oil & Air Filters	MANN+HUMMEL(GERMANY)
Suction Control Group	LUPAMAT(TURKEY) / HOERBIGER(GERMANY)
Electric Components	SCHNEIDER(FRANCE) / MITSUBISHI(JAPAN)
R.P.M of Airend	4255 rpm
Drive System	Belt Driven
Outlet Connection & Cable Size	1 ½" BSP --- 3x(2x16)+10mm ²
Length	1400 mm
Width	1300 mm
Height	1685 mm
Weight	1475 kg
Noise Level	**71 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	1525 kg – 1500 x 1400 x 1850 mm.

* FAD performance measured according to ISO 1217, Annex C-2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

-Lupamat reserves the right to make alterations on given data & compressor design without prior notice

Lupamat

Makina Sanayii A.Ş.

