

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 11/7,5 MITK

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Working Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)*	1,75 m ³ /min.
Shaft Power (at 7,5 bar)	11 kW
Max. Ambient Temperature	40 ^o C
Electric Motor	11 kW/15 hp; 2 Pole (2945 rpm); 400V; 50Hz; IP55; F Insulation; B3 Built; IE3 Class
Cooling System	Air Cooling
Fan Motor & Capacity	0,23 kW; (2700 rpm); 230V; 50Hz; -- 2600/110 (m ³ /h)/Pa
Air Dryer Capacity	2,2 m ³ /min.
Air Tank Capacity	500 L
Airend	SCA8 – TMC(ITALY)
Hydraulic Connections	VITILLO(ITALY)
Cooler	AKG(GERMANY)
Oil & Air Filters	MANN+HUMMEL(GERMANY)
Suction Control Group	VMC (ITALY)
Electric Components	SCHNEIDER(FRANCE) / MITSUBISHI(JAPAN)
R.P.M of Airend	6940 rpm
Drive System	Belt Driven
Outlet Connection & Cable Size	¾" --- 3x(2x4)+2,5+2,5mm ²
Length	1875 mm
Width	800 mm
Height	1700 mm
Weight	598 kg
Noise Level**	65 dB (A)
Oil	Lupamat LPM 68
Max Oil Content	2-3 ppm.(mg/m ³)
Separator Tank	CE Certificated
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	650 Kg. 1980 x 900 x 1850 mm.

* FAD performance measured according to ISO 1217, Annex C-2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

-Lupamat reserves the right to make alterations on given data & compressor design without prior notice

Lupamat

Makina Sanayii A.Ş.


Lupamat
compressor




Lupamat
compressor