

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 22/10 Mi

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	10 bar
Free Air Delivery (at 10 bar)*	3,2 m ³ /min.
Shaft Power (at 10 bar)	22 kW
Max. Ambient Temperature	40°C
Electric Motor	22 kW/30 hp; 2 Pole (2955 rpm); 400V; 50Hz; IP55; IE3 Class; F Insulation; B3 Built
Cooling System	Air Cooling
Fan Motor & Capacity	0,46 kW; (1365 rpm); 400V; 50Hz; --- 4800/125 (m ³ /h)/Pa
Airend	VMX22 R – AERZEN(GERMANY)
Hydraulic Connections	GURSAN(TURKEY) / VITILLO(ITALY)
Cooler	AKG(GERMANY)
Oil & Air Filters	MANN+HUMMEL(GERMANY)
Suction Control Group	LUPAMAT(TURKEY) / HOERBIGER(GERMANY)
Electric Components	SCHNEIDER(FRANCE) / MITSUBISHI(JAPAN)
R.P.M of Airend	3435 rpm
Drive System	Belt Driven
Outlet Connection & Cable Size	¾" --- 3x(2x6)+4mm ²
Length	1400 mm
Width	950 mm
Height	1186 mm
Weight	585 kg
Noise Level**	68 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	620 kg – 1500 x 1050 x 1350 mm.

* FAD performance measured according to ISO 1217, Ed. 4, Annex C-2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

- Lupamat reserves the right to make alterations on given data & compressor design without prior notice

Lupamat
Makina Sanayii A.Ş.

Lupamat
compressor



Lupamat
compressor